

ED8004TCS

HYBRID DVR



HD



H.264



DDNS



Network



PTZ



Audio



MIC



Mobile



CMS



USB



Mouse





E-mail

Main Feature:

- Support 4 CH 2MP@12fps Recording, 1CH 2MP@15fps
- Adopt standard H.264 high profile compression format to get high-quality video at much lower bit rate
- Intuitive and user-friendly Graphic User Interface (GUI), Windows style operation by mouse
- Multi-mode recording: manual / timer / motion / sensor
- Playback: 4 CH simultaneous playback
- Search: time slice, time, event (manual, sensor, motion), tag search
- Express and flexible backup via USB, network and so on
- Pentaplex: preview, record, playback, backup and remote access
- DHCP, DDNS, PPPoE network protocol and CMS supported
- Remote control via IE or CMS: preview, playback, backup, PTZ and configuration
- Dual stream technology for local storage with high definition, remote network transmission and remote surveillance with mobile device
- Multi-user online simultaneously
- Authorization management, log view and device status view
- HDMI output, true high resolution display
- Supports PTZ pre-set and auto cruise, up to 255 pre-sets and 8 cruises
- Supports NAT function and QR-Code scanning by mobile phone and PAD
- Powerful smart phone & Pad surveillance with iOS and Android OS





Model		ED8004TSC	
System	Compression	Standard H.264 High Profile	
Video	Input	BNC x 4, Support TVI & AHD 1080P@25 / 30fps, 720P@25 / 30fps, 960H, D1 Input	
	IP Input	IPC x 1	
	Access Bandwidth	6Mbps	
	Output	HDMI x 1 : 1920 x 1080 / VGA x 1: 1920 x 1080 / CVBS	
Audio	Input	RCA x 1	
	Output	RCA x 1	
	2-Way Audio	Take Up Channel One Audio Input	
Record	Resolution	1080P Lite: 960 x 1080, 720P: 1280 x 720, WD1, D1	
	Frame Rate	1080P	50 fps (PAL) ; 60 fps (NTSC)
		720P	100 fps (PAL) ; 120 fps (NTSC)
		WD1 / D1	100 fps (PAL) ; 120 fps (NTSC)
	Bitrate	1M ~ 3Mbps	
	Encode	VBR / CBR	
	Quality	6 Level	
Mode	Manual, Timer, Motion		
File Manager	Lock, Unlock, Reserving Time		
IP Input	Resolution	1080P / 960P / 720P / WD1	
	Frame Rate	1080P	15 fps
Playback	Playback	4 CH	
	Search	Time / Calendar Search, Event (Motion)	
	Smart Search	High Lighted Date And Time To Display The Channel Record	
	Function	Play, Pause, FF, FB, Digital Zoom	
Alarm	Mode	Motion, Video Loss	
	Input	4 CH	
	Output	1 CH	
	Triggering	Record, PTZ Move, Alarm Out, E-mail, ETC.	
Network	Interface	RJ45 10M/100M Adaptive Ethernet Network Port x 1	
	Protocol	TCP/IP, UDP, HDCP, DNS, PPPOE, DDNS	
	Others	10 Users Online, Dual Stream	
Cell Phone	OS	iPhone, Android	
	Function	Multi-Screen Surveillance (For Certain Model), Record, Snapshot, PTZ Control, Save The Device List	
I/O	HDD	SATA x 1	
	RS485	RS485 x 1, Connect To PTZ Or Keyboard	
	USB	USB 2.0 x 2, One For Mouse, Another For USB Backup Device	
	IR Controller	Optional	
Others	Power Supply	DC 12V	
	Consumption	< 9W (Without HDD)	
	Dimensions	300mm (W) x 270mm (D) x 58mm (H)	
	Work Environment	-10°C ~ 50°C, 10% ~ 90% Humidity	

ALMA TECHNOLOGY SDN. BHD. (1033193-K)

No. 13, Jalan Sakeh 1, 84000 Muar, Johor, Malaysia.
Tel: 1300-88-ALMA (2562), +606-9511314, +6016-7331401 Fax: +606-9541113

Kuala Lumpur Office:
KA 3-2-2, 1st Floor, Kuchai Avenue,
Jln Kuchai Maju 13, Off Jln Kuchai Lama,
Kuchai Entrepreneur Park,

Johor Bahru Office:
No. 101, Jalan Seri Impian 1,
Taman Impian Emas,
81300 Skudai, Johor,

DISTRIBUTOR BY:

